

CSTA

CSTADLL
Version 1.1.3
CSTADLL
Reference Manual

The software described in this document is furnished under a license agreement and may be used only in accordance with the terms of this agreement.

Copyright Notice

Copyright ©1997-2010 Objective Systems, Inc. All rights reserved.

This document may be distributed in any form, electronic or otherwise, provided that it is distributed in its entirety and that the copyright and this notice are included.

Author's Contact Information

Comments, suggestions, and inquiries regarding CSTADLL may be submitted via electronic mail to info@obj-sys.com.

Contents

1	CSTADLL	1
2	Namespace Documentation	3
2.1	Package Com.Objsys.Csta.Common	3
2.1.1	Detailed Description	3
2.2	Package Com.Objsys.Csta.Devices	4
2.2.1	Detailed Description	4
2.3	Package Com.Objsys.Csta.Phase1	5
2.3.1	Detailed Description	5
2.4	Package Com.Objsys.Csta.Phase2	6
2.4.1	Detailed Description	6
2.5	Package Com.Objsys.Csta.Phase3	7
2.5.1	Detailed Description	7
3	Class Documentation	9
3.1	Alcatel4400 Class Reference	9
3.1.1	Detailed Description	9
3.1.2	Constructor & Destructor Documentation	9
3.1.2.1	Alcatel4400	9
3.1.3	Member Function Documentation	9
3.1.3.1	MakeACSEAssociation	9
3.2	AlcatelOXO Class Reference	10
3.2.1	Detailed Description	10
3.2.2	Constructor & Destructor Documentation	10
3.2.2.1	AlcatelOXO	10
3.2.3	Member Function Documentation	10
3.2.3.1	MakeACSEAssociation	10
3.3	CSTARResponseInfo Class Reference	11
3.3.1	Detailed Description	11

3.3.2	Property Documentation	11
3.3.2.1	ResponseFromPBX	11
3.3.2.2	StatusCode	11
3.3.2.3	StatusMessage	11
3.4	GenericCSTAp1 Class Reference	12
3.4.1	Detailed Description	12
3.4.2	Constructor & Destructor Documentation	12
3.4.2.1	GenericCSTAp1	12
3.4.3	Member Function Documentation	12
3.4.3.1	AnswerCall	12
3.4.3.2	DivertCall	12
3.4.3.3	EncodeROSERequestHeader	13
3.4.3.4	MakeACSEAssociation	13
3.4.3.5	MakeCall	13
3.4.3.6	MonitorStart	13
3.4.3.7	MonitorStop	14
3.4.3.8	QueryDevice	14
3.4.3.9	TransferCall	14
3.5	GenericCSTAp2 Class Reference	15
3.5.1	Detailed Description	15
3.5.2	Constructor & Destructor Documentation	15
3.5.2.1	GenericCSTAp2	15
3.5.3	Member Function Documentation	15
3.5.3.1	AnswerCall	15
3.5.3.2	DivertCall	15
3.5.3.3	EncodeROSERequestHeader	16
3.5.3.4	MakeACSEAssociation	16
3.5.3.5	MakeCall	16
3.5.3.6	MonitorStart	16
3.5.3.7	MonitorStop	17
3.5.3.8	QueryDevice	17
3.5.3.9	TransferCall	17
3.6	GenericCSTAp3 Class Reference	18
3.6.1	Detailed Description	18
3.6.2	Constructor & Destructor Documentation	18
3.6.2.1	GenericCSTAp3	18
3.6.3	Member Function Documentation	18

3.6.3.1	AnswerCall	18
3.6.3.2	ClearMessageWaiting	19
3.6.3.3	EncodeROSERequestHeader	19
3.6.3.4	GetSFDevices	19
3.6.3.5	MakeACSEAssociation	19
3.6.3.6	MakeCall	20
3.6.3.7	MonitorStart	20
3.6.3.8	MonitorStop	20
3.6.3.9	ReleaseACSEAssociation	20
3.6.3.10	RingDevice	20
3.6.3.11	SendData	21
3.6.3.12	SetDisplay	21
3.6.3.13	SetMessageWaiting	21
3.6.3.14	SingleStepTransfer	22
3.6.3.15	StartDataPath	22
3.6.3.16	StopDataPath	22
3.6.3.17	StopRing	22
3.6.3.18	TransferCall	23
3.7	IETF_CSTAp1 Class Reference	24
3.7.1	Detailed Description	24
3.7.2	Constructor & Destructor Documentation	24
3.7.2.1	IETF_CSTAp1	24
3.8	IETF_CSTAp2 Class Reference	25
3.8.1	Detailed Description	25
3.8.2	Constructor & Destructor Documentation	25
3.8.2.1	IETF_CSTAp2	25
3.9	IETF_CSTAp3 Class Reference	26
3.9.1	Detailed Description	26
3.9.2	Constructor & Destructor Documentation	26
3.9.2.1	IETF_CSTAp3	26
3.10	LicenseException Class Reference	27
3.10.1	Detailed Description	27
3.11	PanasonicKXTDA Class Reference	28
3.11.1	Detailed Description	28
3.12	PanasonicKXTDE Class Reference	29
3.12.1	Detailed Description	29
3.12.2	Member Function Documentation	29

3.12.2.1	AcquireControlRight	29
3.12.2.2	ClearMessageWaiting	29
3.12.2.3	MakeACSEAssociation	30
3.12.2.4	ReleaseControlRight	30
3.12.2.5	SetMessageWaiting	30
3.13	PanasonicNCP Class Reference	31
3.13.1	Detailed Description	31
3.14	PBXSessionException Class Reference	32
3.14.1	Detailed Description	32
3.15	PBXSessionHelper Class Reference	33
3.15.1	Detailed Description	33
3.15.2	Member Function Documentation	33
3.15.2.1	AsyncCallback	33
3.15.2.2	Close	33
3.15.2.3	Init	34
3.15.2.4	Open	34
3.15.2.5	SendMessage	34
3.15.2.6	SendMessage	34
3.15.2.7	WaitForACSEResponse	34
3.15.2.8	WaitForROSEResponse	35
3.15.3	Property Documentation	35
3.15.3.1	ClientCallback	35
3.15.3.2	DebugMode	35
3.15.3.3	LoggingEnabled	35
3.15.3.4	LoggingFolder	35
3.16	Phase1Opcodes Class Reference	36
3.16.1	Detailed Description	36
3.16.2	Member Enumeration Documentation	36
3.16.2.1	Opcodes	36
3.17	Phase2Opcodes Class Reference	37
3.17.1	Detailed Description	37
3.17.2	Member Enumeration Documentation	37
3.17.2.1	Opcodes	37
3.18	Phase3Opcodes Class Reference	38
3.18.1	Detailed Description	38
3.18.2	Member Enumeration Documentation	38
3.18.2.1	Opcodes	38

3.19	SiemensCap Class Reference	39
3.19.1	Detailed Description	39
3.19.2	Member Function Documentation	39
3.19.2.1	MakeACSEAssociation	39
3.20	SiemensHicom300 Class Reference	40
3.20.1	Detailed Description	40
3.20.2	Constructor & Destructor Documentation	40
3.20.2.1	SiemensHicom300	40
3.21	SiemensHipath3000p2 Class Reference	41
3.21.1	Detailed Description	41
3.21.2	Constructor & Destructor Documentation	41
3.21.2.1	SiemensHipath3000p2	41
3.22	SiemensHipath3000p3 Class Reference	42
3.22.1	Detailed Description	42
3.22.2	Constructor & Destructor Documentation	42
3.22.2.1	SiemensHipath3000p3	42
3.22.3	Member Function Documentation	42
3.22.3.1	MakeACSEAssociation	42
3.23	SiemensHipath4000 Class Reference	43
3.23.1	Detailed Description	43
3.24	SiemensRealitis Class Reference	44
3.24.1	Detailed Description	44
3.25	SingleStepTransferInfo Class Reference	45
3.25.1	Detailed Description	45
3.25.2	Property Documentation	45
3.25.2.1	TransferFromDevice	45
3.25.2.2	TransferringCallID	45
3.25.2.3	TransferToDevice	45
3.26	SocketState Class Reference	46
3.26.1	Detailed Description	46
3.26.2	Property Documentation	46
3.26.2.1	ReadBuffer	46
3.26.2.2	TotalLength	46
3.27	TadiranCoral Class Reference	47
3.27.1	Detailed Description	47
3.28	TransferCallInfo Class Reference	48
3.28.1	Detailed Description	48

3.28.2	Property Documentation	48
3.28.2.1	ActiveDeviceCallID	48
3.28.2.2	ActiveDeviceNumber	48
3.28.2.3	ConnectedDevice	48
3.28.2.4	HeldDevice	48
3.28.2.5	HeldDeviceCallID	48
3.28.2.6	HeldDeviceNumber	48

Chapter 1

CSTADLL

The CSTADLL product is a Microsoft .NET 2.0 DLL that allows client code to use a single library to communicate with a PBX device, regardless of what CSTA phase that device uses.

The DLL uses the following namespaces:

- `Com.Objsys.Csta.Common`
- `Com.Objsys.Csta.Devices`
- `Com.Objsys.Csta.Phase1`
- `Com.Objsys.Csta.Phase2`
- `Com.Objsys.Csta.Phase3`

The `Com.Objsys.Csta.Common` namespace contains classes that are common to all CSTA phases.

The `Com.Objsys.Csta.Devices` namespace contains classes that allow a caller to use specific PBX devices.

The `Com.Objsys.Csta.Phase(n)` namespaces contain classes that are specific to the indicated phase. Most of these classes are generated by ASN1C from the CSTA and ACSE ASN.1 specifications. These generated classes are not documented here, but you can consult the ASN1C C# User Guide for information about how ASN.1 constructions are translated into C# classes.

Each namespace also contains several classes that are not generated by ASN1C. These classes are the ones documented in this manual.

The DLL allows a client to have a session with a single PBX system, during which the client can send ACSE and CSTA messages to the PBX and receive responses.

The typical way to use the DLL is to use the `PBXSessionHelper` class to set up the communication to the PBX system via the `Init` method. If the PBX will be sending asynchronous data, such as monitor packets, to the client, the `ClientCallback` property can be used to define a callback method to receive the asynchronous data. If no callback method is defined, asynchronous data will be ignored.

The CSTADLL kit includes several samples to guide you in writing your own code. The name of the sample conveys some information about the sample. If the name of the sample starts with DLL, it means the sample shows how to use one of the helper methods that the DLL exposes. If the name of the sample starts with CSTA, then that sample still shows a way to make use of the DLL, but instead of using one of the DLL's helper methods, the sample instead shows how to use the DLL to send to a PBX a CSTA message for which the DLL doesn't expose a helper method.

After either DLL or CSTA in the sample name is an indicator of what language the sample is written in. Cs is used to indicate that the sample is written in C#. Vb will be used to indicate that the sample is written in Visual BASIC.

Similar codes will be used if samples are provided in other languages; e.g., perhaps CppCLI for samples written in C++/CLI.

For example, the sample `DLLCsAnswerCall` is a sample that shows how to use one of the DLL's helper methods in C# to instruct a PBX to answer a call. The sample `CSTACsClearConnection` shows how to use the DLL with C# to send a PBX the CSTA `ClearConnection` message, for which there is no exposed helper method.

The classes and methods exposed by the all-phases DLL within the `CSTADLL` package are probably sufficient to handle ACSE and CSTA operations for most PBX devices. But if needed, you can write a class of your own to handle ACSE and CSTA operations for a PBX device that the `CSTADLL` software doesn't explicitly support. The sample `DLLCsNewPBX` shows how this might be accomplished. This sample contains code for a small separate DLL that could be used to support a fictitious PBX device called the `AwesomePBX100`. The assumption in the sample is that this device uses standard phase 2 messages for all operations except for the ACSE make association message. This message is the one message that is most commonly different from one PBX to the next. The `DLLCsNewPBX` sample shows how the `MakeACSEAssociation` method within the `GenericCSTAp2` class can be overridden in a class that you can write. The override implementation handles the details that are specific to the device. Other methods within `GenericCSTAp2` could also be overridden as needed.

The all-phases DLL can log message traffic between a client program and the PBX device if so desired. The logging is controlled by the `LoggingEnabled` property with the `PBXSessionHelper` class. The logging is off by default. Both of the provided sample clients enable the logging. The log file used is named `cstadll_<program>.log`, where `<program>` is the name of the executable image that is using the DLL. The location of the log file is the folder where the executable image resides. If the log file grows to more than 5 Mb, it is copied to `cstadll_<program>.backup.log`, and a new log file is opened. If there is already a file with the backup file name, it is overwritten.

Chapter 2

Namespace Documentation

2.1 Package `Com.Objsys.Csta.Common`

Classes

- class [CSTAResponseInfo](#)
- class [LicenseException](#)
- class [PBXSessionException](#)
- class [PBXSessionHelper](#)
- class [SocketState](#)

2.1.1 Detailed Description

The namespace `Com.Objsys.Csta.Common` contains classes that are common to all phases.

2.2 Package Com.Objsys.Csta.Devices

Classes

- class [Alcatel4400](#)
- class [AlcatelOXO](#)
- class [PanasonicKXTDA](#)
- class [PanasonicKXTDE](#)
- class [PanasonicNCP](#)
- class [SiemensCap](#)
- class [SiemensHicom300](#)
- class [SiemensHipath3000p2](#)
- class [SiemensHipath3000p3](#)
- class [SiemensHipath4000](#)
- class [SiemensRealitis](#)
- class [TadiranCoral](#)

2.2.1 Detailed Description

The namespace `Com.Objsys.Csta.Devices` contains classes that allow a caller to use specific PBX devices. The caller does not need to know what CSTA phase a device uses unless the device can accept messages formatted according to rules from more than one CSTA phase. In that case the class name ends with 'p(n)', where (n) is the number of the phase.

2.3 Package Com.Objsys.Csta.Phase1

Classes

- class [GenericCSTAp1](#)
- class [IETF_CSTAp1](#)
- class [Phase1OpCodes](#)

2.3.1 Detailed Description

The namespace [Com.Objsys.Csta.Phase1](#) contains classes that are specific to phase 1. Most of these classes are generated by ASN1C from the CSTA and ACSE ASN.1 specifications. These generated classes are not documented here, but you can consult the ASN1C C# User Guide for information about how ASN.1 constructions are translated into C# classes.

The namespace also contains several classes that are not generated by ASN1C. These classes are the ones documented in this manual.

2.4 Package Com.Objsys.Csta.Phase2

Classes

- class [GenericCSTAp2](#)
- class [IETF_CSTAp2](#)
- class [Phase2Opcodes](#)

2.4.1 Detailed Description

The namespace [Com.Objsys.Csta.Phase2](#) contains classes that are specific to phase 2. Most of these classes are generated by ASN1C from the CSTA and ACSE ASN.1 specifications. These generated classes are not documented here, but you can consult the ASN1C C# User Guide for information about how ASN.1 constructions are translated into C# classes.

The namespace also contains several classes that are not generated by ASN1C. These classes are the ones documented in this manual.

2.5 Package Com.Objsys.Csta.Phase3

Classes

- class [GenericCSTAp3](#)
- class [IETF_CSTAp3](#)
- class [Phase3OpCodes](#)
- class [SingleStepTransferInfo](#)
- class [TransferCallInfo](#)

2.5.1 Detailed Description

The namespace [Com.Objsys.Csta.Phase3](#) contains classes that are specific to phase 3. Most of these classes are generated by ASN1C from the CSTA and ACSE ASN.1 specifications. These generated classes are not documented here, but you can consult the ASN1C C# User Guide for information about how ASN.1 constructions are translated into C# classes.

The namespace also contains several classes that are not generated by ASN1C. These classes are the ones documented in this manual.

Chapter 3

Class Documentation

3.1 Alcatel4400 Class Reference

Inherits [Com::Objsys::Csta::Phase2::IETF_CSTAp2](#).

Public Member Functions

- [Alcatel4400 \(\)](#)
- override [CSTAResponseInfo MakeACSEAssociation \(\)](#)

3.1.1 Detailed Description

Implements CSTA phase 2 operations for the Alcatel 4400 PBX device.

3.1.2 Constructor & Destructor Documentation

3.1.2.1 Alcatel4400 ()

Default constructor.

3.1.3 Member Function Documentation

3.1.3.1 override CSTAResponseInfo MakeACSEAssociation () [virtual]

Establish an ACSE association with the PBX.

Returns

A CSTAResponseInfo object.

Reimplemented from [GenericCSTAp2](#).

3.2 AlcatelOXO Class Reference

Inherits [Com::Objsys::Csta::Phase2::IETF_CSTAp2](#).

Public Member Functions

- [AlcatelOXO \(\)](#)
- override [CSTAResponseInfo MakeACSEAssociation \(\)](#)

3.2.1 Detailed Description

Implements CSTA phase 2 operations for the Alcatel OXO device.

3.2.2 Constructor & Destructor Documentation

3.2.2.1 AlcatelOXO ()

Default constructor.

3.2.3 Member Function Documentation

3.2.3.1 override [CSTAResponseInfo MakeACSEAssociation \(\)](#) [virtual]

Establish an ACSE association with the PBX.

Returns

A [CSTAResponseInfo](#) object.

Reimplemented from [GenericCSTAp2](#).

3.3 CSTAResponseInfo Class Reference

Properties

- byte[] [ResponseFromPBX](#) [get, set]
- int [StatusCode](#) [get, set]
- string [StatusMessage](#) [get, set]

3.3.1 Detailed Description

Contains information about a PBX operation that was attempted.

3.3.2 Property Documentation

3.3.2.1 byte [] ResponseFromPBX [get, set]

Contains the response from the PBX.

3.3.2.2 int StatusCode [get, set]

A numeric status code. A value less than zero indicates that something went wrong during the attempted operation.

3.3.2.3 string StatusMessage [get, set]

Text containing information about a PBX operation that has completed, either successfully or not.

3.4 GenericCSTAp1 Class Reference

Inherited by [SiemensHicom300](#), and [IETF_CSTAp1](#).

Public Member Functions

- virtual [CSTARResponseInfo AnswerCall](#) (string deviceToLift)
- virtual [CSTARResponseInfo DivertCall](#) (string divertFrom, string divertTo)
- int [EncodeROSERequestHeader](#) ([CSTARResponseInfo](#) response, [Asn1BerEncodeBuffer](#) encodeBuffer, [Phase1Opcodes.Opcodes](#) opcode, out InvokeId savedInvokeId)
- [GenericCSTAp1](#) ()
- virtual [CSTARResponseInfo MakeACSEAssociation](#) ()
- virtual [CSTARResponseInfo MakeCall](#) (string callingDevice, string calledDevice)
- virtual [CSTARResponseInfo MonitorStart](#) (string deviceToMonitor)
- virtual [CSTARResponseInfo MonitorStop](#) (int crossRefId)
- virtual [CSTARResponseInfo QueryDevice](#) (string deviceToQuery)
- virtual [CSTARResponseInfo TransferCall](#) (string heldDevice, string connectedDevice)

3.4.1 Detailed Description

Implements CSTA phase 1 operations using BER.

3.4.2 Constructor & Destructor Documentation

3.4.2.1 [GenericCSTAp1](#) ()

Default constructor. Indicates that phase 1 is in effect.

3.4.3 Member Function Documentation

3.4.3.1 [virtual CSTARResponseInfo AnswerCall](#) (string *deviceToLift*) [**virtual**]

Answers a call.

Parameters

deviceToLift The identification (e.g., phone number) of the device to answer.

Returns

A [CSTARResponseInfo](#) object.

3.4.3.2 [virtual CSTARResponseInfo DivertCall](#) (string *divertFrom*, string *divertTo*) [**virtual**]

Diverts a call from a source to a destination.

Parameters

divertFrom Identifier (e.g., phone number) of the call to be diverted.

divertTo Identifier (e.g., phone number) of the location to which the call is to be diverted.

Returns

A CSTAResponseInfo object.

3.4.3.3 int EncodeROSERequestHeader (CSTAResponseInfo *response*, Asn1BerEncodeBuffer *encodeBuffer*, Phase1Opcodes.Opcodes *opcode*, out InvokeId *savedInvokeId*)

This method prepends a ROSE header to an already encoded phase 1 CSTA message.

Parameters

response A CSTAResponseInfo object, used to communicate any exception information back to the caller.

encodeBuffer An Asn1BerEncodeBuffer instance containing the already encoded CSTA message.

opcode The opcode enumeration for the operation that the encoded CSTA message describes.

savedInvokeId An InvokeId object variable that will get populated with the reference to the InvokeId object that gets encoded into the ROSE header. This is used when the response is received to match the response with the request.

Returns

The length of the encoded message, including both the CSTA message and the ROSE header, or -1 if the encoding fails.

3.4.3.4 virtual CSTAResponseInfo MakeACSEAssociation () [virtual]

Establish an ACSE association with the PBX.

Returns

A CSTAResponseInfo object.

3.4.3.5 virtual CSTAResponseInfo MakeCall (string *callingDevice*, string *calledDevice*) [virtual]

Instruct the PBX to place a call.

Parameters

callingDevice Identifier (e.g., phone number) of the device making the call.

calledDevice Identifier (e.g., phone number) of the device being called.

Returns

A CSTAResponseInfo object.

3.4.3.6 virtual CSTAResponseInfo MonitorStart (string *deviceToMonitor*) [virtual]

Issues a MonitorStart request to the PBX.

Parameters

deviceToMonitor Identifier (e.g., telephone number) of the device to monitor.

Returns

A CSTAResponseInfo object.

3.4.3.7 virtual CSTAResponseInfo MonitorStop (int *crossRefId*) [virtual]

Stop a previously started PBX monitor request.

Parameters

crossRefId The cross reference id of the monitor request.

Returns

A CSTAResponseInfo object.

3.4.3.8 virtual CSTAResponseInfo QueryDevice (string *deviceToQuery*) [virtual]

Queries a device.

Parameters

deviceToQuery The identification (e.g., phone number) of the device to query.

Returns

A CSTAResponseInfo object.

3.4.3.9 virtual CSTAResponseInfo TransferCall (string *heldDevice*, string *connectedDevice*) [virtual]

Transfers a call from one device to another.

Parameters

heldDevice Identifier (e.g., phone number) of the device from which the call is transferred.

connectedDevice Identifier (e.g., phone number) of the device to which the call is transferred.

Returns

A CSTAResponseInfo object.

3.5 GenericCSTAp2 Class Reference

Inherited by [SiemensHipath3000p2](#), and [IETF_CSTAp2](#).

Public Member Functions

- virtual [CSTARResponseInfo AnswerCall](#) (string deviceToLift)
- virtual [CSTARResponseInfo DivertCall](#) (string divertFrom, string divertTo)
- int [EncodeROSERequestHeader](#) ([CSTARResponseInfo](#) response, Asn1BerEncodeBuffer encodeBuffer, [Phase2Opcodes.Opcodes](#) opcode, out InvokeId savedInvokeId)
- [GenericCSTAp2](#) ()
- virtual [CSTARResponseInfo MakeACSEAssociation](#) ()
- virtual [CSTARResponseInfo MakeCall](#) (string callingDevice, string calledDevice)
- virtual [CSTARResponseInfo MonitorStart](#) (string deviceToMonitor)
- virtual [CSTARResponseInfo MonitorStop](#) (int crossRefId)
- virtual [CSTARResponseInfo QueryDevice](#) (string deviceToQuery)
- virtual [CSTARResponseInfo TransferCall](#) (string heldDevice, string connectedDevice)

3.5.1 Detailed Description

Implements CSTA phase 2 operations using BER.

3.5.2 Constructor & Destructor Documentation

3.5.2.1 [GenericCSTAp2](#) ()

Default constructor. Indicates that phase 2 is in effect.

3.5.3 Member Function Documentation

3.5.3.1 [virtual CSTARResponseInfo AnswerCall](#) (string *deviceToLift*) [**virtual**]

Answers a call.

Parameters

deviceToLift The identification (e.g., phone number) of the device to answer.

Returns

A [CSTARResponseInfo](#) object.

3.5.3.2 [virtual CSTARResponseInfo DivertCall](#) (string *divertFrom*, string *divertTo*) [**virtual**]

Diverts a call from a source to a destination.

Parameters

divertFrom Identifier (e.g., phone number) of the call to be diverted.

divertTo Identifier (e.g., phone number) of the location to which the call is to be diverted.

Returns

A CSTAResponseInfo object.

3.5.3.3 int EncodeROSERequestHeader (CSTAResponseInfo *response*, Asn1BerEncodeBuffer *encodeBuffer*, Phase2Opcodes.Opcodes *opcode*, out InvokeId *savedInvokeId*)

This method prepends a ROSE header to an already encoded phase 2 CSTA message.

Parameters

response A CSTAResponseInfo object, used to communicate any exception information back to the caller.

encodeBuffer An Asn1BerEncodeBuffer instance containing the already encoded CSTA message.

opcode The opcode enumeration for the operation that the encoded CSTA message describes.

savedInvokeId An InvokeId object variable that will get populated with the reference to the InvokeId object that gets encoded into the ROSE header. This is used when the response is received to match the response with the request.

Returns

The length of the encoded message, including both the CSTA message and the ROSE header, or -1 if the encoding fails.

3.5.3.4 virtual CSTAResponseInfo MakeACSEAssociation () [virtual]

Establish an ACSE association with the PBX.

Returns

A CSTAResponseInfo object.

Reimplemented in [Alcatel4400](#), and [AlcatelOXO](#).

3.5.3.5 virtual CSTAResponseInfo MakeCall (string *callingDevice*, string *calledDevice*) [virtual]

Instruct the PBX to place a call.

Parameters

callingDevice Identifier (e.g., phone number) of the device making the call.

calledDevice Identifier (e.g., phone number) of the device being called.

Returns

A CSTAResponseInfo object.

3.5.3.6 virtual CSTAResponseInfo MonitorStart (string *deviceToMonitor*) [virtual]

Issues a MonitorStart request to the PBX.

Parameters

deviceToMonitor Identifier (e.g., telephone number) of the device to monitor.

Returns

A CSTAResponseInfo object.

3.5.3.7 virtual CSTAResponseInfo MonitorStop (int *crossRefId*) [virtual]

Stop a previously started PBX monitor request.

Parameters

crossRefId The cross reference id of the monitor request.

Returns

A CSTAResponseInfo object.

3.5.3.8 virtual CSTAResponseInfo QueryDevice (string *deviceToQuery*) [virtual]

Queries a device.

Parameters

deviceToQuery The identification (e.g., phone number) of the device to query.

Returns

A CSTAResponseInfo object.

3.5.3.9 virtual CSTAResponseInfo TransferCall (string *heldDevice*, string *connectedDevice*) [virtual]

Transfers a call from one device to another.

Parameters

heldDevice Identifier (e.g., phone number) of the device from which the call is transferred.

connectedDevice Identifier (e.g., phone number) of the device to which the call is transferred.

Returns

A CSTAResponseInfo object.

3.6 GenericCSTAp3 Class Reference

Inherited by [SiemensHipath3000p3](#), and [IETF_CSTAp3](#).

Public Member Functions

- virtual [CSTARResponseInfo AnswerCall](#) (string deviceToLift)
- virtual [CSTARResponseInfo ClearMessageWaiting](#) (string targetDevice)
- virtual int [EncodeROSERequestHeader](#) ([CSTARResponseInfo](#) response, [Asn1BerEncodeBuffer](#) encodeBuffer, [Phase3Opcodes.Opcodes](#) opcode, out InvokeId savedInvokeId)
- [GenericCSTAp3](#) ()
- virtual [CSTARResponseInfo GetSFDevices](#) ()
- virtual [CSTARResponseInfo MakeACSEAssociation](#) ()
- virtual [CSTARResponseInfo MakeCall](#) (string callingDevice, string calledDevice)
- virtual [CSTARResponseInfo MonitorStart](#) (string deviceToMonitor)
- virtual [CSTARResponseInfo MonitorStop](#) (int crossRefId)
- virtual [CSTARResponseInfo ReleaseACSEAssociation](#) ()
- virtual [CSTARResponseInfo RingDevice](#) (string targetDevice, string targetRinger, long ringPattern)
- virtual [CSTARResponseInfo SendData](#) ([IOCrossRefID](#) ioCrossRef, string text)
- virtual [CSTARResponseInfo SetDisplay](#) (string targetDevice, string text)
- virtual [CSTARResponseInfo SetMessageWaiting](#) (string targetDevice)
- virtual [CSTARResponseInfo SingleStepTransfer](#) ([SingleStepTransferInfo](#) sstInfo)
- virtual [CSTARResponseInfo StartDataPath](#) (string targetDevice)
- virtual [CSTARResponseInfo StopDataPath](#) ([IOCrossRefID](#) ioCrossRef)
- virtual [CSTARResponseInfo StopRing](#) (string targetDevice, string targetRinger, long ringPattern)
- virtual [CSTARResponseInfo TransferCall](#) ([TransferCallInfo](#) tcInfo)

3.6.1 Detailed Description

Implements CSTA phase 3 operations using BER.

3.6.2 Constructor & Destructor Documentation

3.6.2.1 [GenericCSTAp3](#) ()

Default constructor. Indicates that phase 3 is in effect.

3.6.3 Member Function Documentation

3.6.3.1 virtual [CSTARResponseInfo AnswerCall](#) (string *deviceToLift*) [virtual]

Answers a call.

Parameters

deviceToLift The identification (e.g., phone number) of the device to answer.

Returns

A [CSTARResponseInfo](#) object.

3.6.3.2 virtual CSTAResponseInfo ClearMessageWaiting (string *targetDevice*) [virtual]

Turns off the message waiting indicator on a device's display.

Parameters

targetDevice The device for which the indicator is to be turned off.

Returns

A CSTAResponseInfo object.

3.6.3.3 virtual int EncodeROSERequestHeader (CSTAResponseInfo *response*, Asn1BerEncodeBuffer *encodeBuffer*, Phase3Opcodes.Opcodes *opcode*, out InvokeId *savedInvokeId*) [virtual]

This method prepends a ROSE header to an already encoded phase 3 CSTA message.

Parameters

response A CSTAResponseInfo object, used to communicate any exception information back to the caller.

encodeBuffer An Asn1BerEncodeBuffer instance containing the already encoded CSTA message.

opcode The opcode enumeration for the operation that the encoded CSTA message describes.

savedInvokeId An InvokeId object variable that will get populated with the reference to the InvokeId object that gets encoded into the ROSE header. This is used when the response is received to match the response with the request.

Returns

The length of the encoded message, including both the CSTA message and the ROSE header, or -1 if the encoding fails.

3.6.3.4 virtual CSTAResponseInfo GetSFDevices () [virtual]

Sends a Get Switching Function [Devices](#) request to the PBX.

Returns

A CSTAResponseInfo object.

3.6.3.5 virtual CSTAResponseInfo MakeACSEAssociation () [virtual]

Establish an ACSE association with the PBX.

Returns

A CSTAResponseInfo object.

Reimplemented in [PanasonicKXTDE](#), [SiemensCap](#), and [SiemensHipath3000p3](#).

3.6.3.6 virtual CSTAResponseInfo MakeCall (string *callingDevice*, string *calledDevice*) [virtual]

Instruct the PBX to place a call.

Parameters

callingDevice Identifier (e.g., phone number) of the device making the call.

calledDevice Identifier (e.g., phone number) of the device being called.

Returns

A CSTAResponseInfo object.

3.6.3.7 virtual CSTAResponseInfo MonitorStart (string *deviceToMonitor*) [virtual]

Issues a MonitorStart request to the PBX.

Parameters

deviceToMonitor Identifier (e.g., telephone number) of the device to monitor.

Returns

A CSTAResponseInfo object.

3.6.3.8 virtual CSTAResponseInfo MonitorStop (int *crossRefId*) [virtual]

Stop a previously started PBX monitor request.

Parameters

crossRefId The cross reference id of the monitor request.

Returns

A CSTAResponseInfo object.

3.6.3.9 virtual CSTAResponseInfo ReleaseACSEAssociation () [virtual]

Releases an ACSE association with a PBX device.

Returns

A CSTAResponseInfo object.

3.6.3.10 virtual CSTAResponseInfo RingDevice (string *targetDevice*, string *targetRinger*, long *ringPattern*) [virtual]

Causes a telephony device to ring.

Parameters

targetDevice The device to ring.

targetRinger The id of the ringer to use for the ring. This argument can be specified as a character string (e.g. "abc"), a hex string (e.g. "010A05'H"), or a binary string (e.g. "000000010000101000000101'B").

ringPattern The indicator of the ring pattern to use.

Returns

A CSTAResponseInfo object.

3.6.3.11 virtual CSTAResponseInfo SendData (IOCrossRefID *ioCrossRef*, string *text*) [virtual]

Sends a text message to a telephony device.

Parameters

ioCrossRef An IOCrossRefID object, most likely obtained by a previous call to StartDataPath.

text The text to send to the telephony device.

Returns

A CSTAResponseInfo object.

3.6.3.12 virtual CSTAResponseInfo SetDisplay (string *targetDevice*, string *text*) [virtual]

Sends text to a telephony device's display

Parameters

targetDevice The device to which the text is to be sent.

text The text to be sent.

Returns

A CSTAResponseInfo object.

3.6.3.13 virtual CSTAResponseInfo SetMessageWaiting (string *targetDevice*) [virtual]

Turns on the message waiting indicator on a device's display.

Parameters

targetDevice The device for which the indicator is to be turned on.

Returns

A CSTAResponseInfo object.

3.6.3.14 virtual CSTAResponseInfo SingleStepTransfer (SingleStepTransferInfo *sstInfo*) [virtual]

Perform a single step transfer.

Parameters

sstInfo A [SingleStepTransferInfo](#) object.

Returns

A CSTAResponseInfo object.

3.6.3.15 virtual CSTAResponseInfo StartDataPath (string *targetDevice*) [virtual]

Opens up a data path to a specified device.

Parameters

targetDevice Specifies the device to which a data path is to be opened.

Returns

A CSTAResponseInfo object.

3.6.3.16 virtual CSTAResponseInfo StopDataPath (IOCrossRefID *ioCrossRef*) [virtual]

Stops a previously established data path

Parameters

ioCrossRef An IOCrossRef object, most likely obtained from a previous call to StartDataPath.

Returns

A CSTAResponseInfo object.

3.6.3.17 virtual CSTAResponseInfo StopRing (string *targetDevice*, string *targetRinger*, long *ringPattern*) [virtual]

Stops a ringer on a telephony device.

Parameters

targetDevice The device for which the ringer is to stop.

targetRinger The id of the ringer to stop. This argument can be specified as a character string (e.g, "abc"), a hex string (e.g, "'010A05'H"), or a binary string (e.g, "'000000010000101000000101'B").

ringPattern The indicator of the ring pattern to stop.

Returns

A CSTAResponseInfo object.

3.6.3.18 virtual CSTAResponseInfo TransferCall (TransferCallInfo *tcInfo*) [virtual]

Transfers a call from one device to another.

Parameters

tcInfo A [TransferCallInfo](#) object.

Returns

A CSTAResponseInfo object.

3.7 IETF_CSTAp1 Class Reference

Inherits [Com::Objsys::Csta::Phase1::GenericCSTAp1](#).

Inherited by [SiemensRealitis](#), and [TadiranCoral](#).

Public Member Functions

- [IETF_CSTAp1 \(\)](#)

3.7.1 Detailed Description

Implements CSTA phase 1 operations using IETF encoding, which puts a two-byte length in front of the BER message.

3.7.2 Constructor & Destructor Documentation

3.7.2.1 IETF_CSTAp1 ()

Default constructor. Indicates to the PBXSession that IETF is in effect.

3.8 IETF_CSTAp2 Class Reference

Inherits [Com::Objsys::Csta::Phase2::GenericCSTAp2](#).

Inherited by [Alcatel4400](#), and [AlcatelOXO](#).

Public Member Functions

- [IETF_CSTAp2 \(\)](#)

3.8.1 Detailed Description

Implements CSTA phase 2 operations using IETF encoding, which puts a two-byte length in front of the BER message.

3.8.2 Constructor & Destructor Documentation

3.8.2.1 IETF_CSTAp2 ()

Default constructor. Indicates to the PBXSession that IETF is in effect.

3.9 IETF_CSTAp3 Class Reference

Inherits [Com::Objsys::Csta::Phase3::GenericCSTAp3](#).

Inherited by [PanasonicKXTDE](#), and [SiemensCap](#).

Public Member Functions

- [IETF_CSTAp3](#) ()

3.9.1 Detailed Description

Implements CSTA phase 3 operations using IETF encoding, which puts a two-byte length in front of the BER message.

3.9.2 Constructor & Destructor Documentation

3.9.2.1 IETF_CSTAp3 ()

Default constructor. Indicates to the PBXSession that IETF is in effect.

3.10 LicenseException Class Reference

3.10.1 Detailed Description

Defines an exception that occurs while trying to find license information.

3.11 PanasonicKXTDA Class Reference

Inherits [Com::Objsys::Csta::Devices::PanasonicKXTDE](#).

3.11.1 Detailed Description

Implements CSTA phase 3 operations for the Panasonic KX-TDA PBX device.

3.12 PanasonicKXTDE Class Reference

Inherits [Com::Objsys::Csta::Phase3::IETF_CSTAp3](#).

Inherited by [PanasonicKXTDA](#), and [PanasonicNCP](#).

Public Member Functions

- [CSTARResponseInfo AcquireControlRight](#) (string *targetDevice*)
- [CSTARResponseInfo ClearMessageWaiting](#) (string *originatingDevice*, string *targetDevice*)
- override [CSTARResponseInfo MakeACSEAssociation](#) ()
- [CSTARResponseInfo ReleaseControlRight](#) (string *targetDevice*)
- [CSTARResponseInfo SetMessageWaiting](#) (string *originatingDevice*, string *targetDevice*)

3.12.1 Detailed Description

Implements CSTA phase 3 operations for the Panasonic KX-TDE PBX device.

3.12.2 Member Function Documentation

3.12.2.1 [CSTARResponseInfo AcquireControlRight](#) (string *targetDevice*)

Acquires the right to control a telephony device. This method will cause a "PDF (Physical Device Feature) Start" Escape message to be sent to the PBX.

Parameters

targetDevice The target telephony device.

Returns

A [CSTARResponseInfo](#) object.

3.12.2.2 [CSTARResponseInfo ClearMessageWaiting](#) (string *originatingDevice*, string *targetDevice*)

Turns off a device's message waiting indicator.

Parameters

originatingDevice The device that originated the call back request.

targetDevice The device for which the message waiting indicator is to be turned off.

Returns

A [CSTARResponseInfo](#) object.

3.12.2.3 **override CSTAResponseInfo MakeACSEAssociation () [virtual]**

Establish an ACSE association with the PBX.

Returns

A CSTAResponseInfo object.

Reimplemented from [GenericCSTAp3](#).

3.12.2.4 **CSTAResponseInfo ReleaseControlRight (string *targetDevice*)**

Releases the right to control a telephony device. This method will cause a "PDF (Physical Device Feature) Stop" Escape message to be sent to the PBX.

Parameters

targetDevice The target telephony device.

Returns

A CSTAResponseInfo object.

3.12.2.5 **CSTAResponseInfo SetMessageWaiting (string *originatingDevice*, string *targetDevice*)**

Turns on a device's message waiting indicator.

Parameters

originatingDevice The device that originated the call back request.

targetDevice The device for which the message waiting indicator is to be turned on.

Returns

A CSTAResponseInfo object.

3.13 PanasonicNCP Class Reference

Inherits [Com::Objsys::Csta::Devices::PanasonicKXTDE](#).

3.13.1 Detailed Description

Implements CSTA phase 3 operations for the Panasonic NCP PBX device.

3.14 PBXSessionException Class Reference

3.14.1 Detailed Description

Defines an exception that occurs while communicating with a PBX.

3.15 PBXSessionHelper Class Reference

Public Member Functions

- delegate void [AsyncCallback](#) (byte[] asyncData)

Static Public Member Functions

- static void [Close](#) ()
- static void [Init](#) (string pbxSystem, int port)
- static void [Open](#) ()
- static void [SendMessage](#) (string messageType, byte[] message, int messageLength, Asn1Choice invokeId)
- static void [SendMessage](#) (byte[] message, int messageLength, Asn1Choice invokeId)
- static [SocketState](#) [WaitForACSEResponse](#) ()
- static [SocketState](#) [WaitForROSEResponse](#) (Asn1Choice invokeId)

Properties

- static AsyncCallback [ClientCallback](#) [get, set]
- static bool [DebugMode](#) [get, set]
- static bool [LoggingEnabled](#) [get, set]
- static string [LoggingFolder](#) [get, set]

3.15.1 Detailed Description

Manages the communication with the PBX. This class is a static helper class that allows a client of the DLL to communicate with a single PBX.

3.15.2 Member Function Documentation

3.15.2.1 delegate void AsyncCallback (byte[] asyncData)

Declaration of a callback function to be invoked when an asynchronous message is received, such as from a monitor session.

Parameters

asyncData The data received asynchronously from the PBX.

3.15.2.2 static void Close () [static]

Terminates the session to the PBX. This method can be used to terminate sessions with PBX devices that don't accept ACSE release association requests.

3.15.2.3 static void Init (string *pbxSystem*, int *port*) [static]

Initializes the PBX Session.

Parameters

- pbxSystem* The name or IP address of the PBX system.
- port* The port on the PBX system to which the client is connecting.

3.15.2.4 static void Open () [static]

This method can be used to establish communication with a PBX device before any messages are actually sent to the device.

3.15.2.5 static void SendMessage (string *messageType*, byte[] *message*, int *messageLength*, Asn1Choice *invokeId*) [static]

This method sends a message to the PBX using TCP/IP.

Parameters

- messageType* A string token to help identify the message in the CSTADLL log file.
- message* Byte array containing the encoded message to send.
- messageLength* The length of the encoded message.
- invokeId* The invoke id object from the message's ROSE header. This parameter is cast up to Asn1Choice since this method is phase-independent, and the InvokeId classes for all three phases derive from the Asn1Choice class in the ASN1C C# runtime.

3.15.2.6 static void SendMessage (byte[] *message*, int *messageLength*, Asn1Choice *invokeId*) [static]

This method sends a message to the PBX using TCP/IP.

Parameters

- message* Byte array containing the encoded message to send.
- messageLength* The length of the encoded message.
- invokeId* The invoke id object from the message's ROSE header. This parameter is cast up to Asn1Choice since this method is phase-independent, and the InvokeId classes for all three phases derive from the Asn1Choice class in the ASN1C C# runtime.

3.15.2.7 static SocketState WaitForACSEResponse () [static]

This method waits for a response to an ACSE message. ACSE messages do not have the ROSE header.

Returns

- A [SocketState](#) instance that contains the response that comes back from the PBX.

3.15.2.8 static SocketState WaitForROSEResponse (Asn1Choice *invokeId*) [static]

This method waits for a response to a CSTA message sent with a ROSE header.

Parameters

invokeId The invoke id object that was encoded into the ROSE header. This is used to match received messages back to the sending message. The parameter is cast up to Asn1Choice because this method is phase-independent, and the InvokeId classes for all three phases derive from the Asn1Choice class in the ASN1C C# runtime.

Returns

A [SocketState](#) instance that contains the response that comes back from the PBX.

3.15.3 Property Documentation

3.15.3.1 AsyncCallback ClientCallback [static, get, set]

Holds a reference to an asynchronous callback function. This function will be invoked if data is received asynchronously from the PBX, such as from a monitor operation.

3.15.3.2 bool DebugMode [static, get, set]

Enables behavior that facilitates debugging of the CSTADLL software. This property is most likely useful only to Objective Systems staff.

3.15.3.3 bool LoggingEnabled [static, get, set]

Determines whether logging of traffic between the client and the PBX will be done.

3.15.3.4 string LoggingFolder [static, get, set]

Specifies a folder to receive the log file. If not specified, the log file will go into whatever folder the calling .exe resides in.

3.16 Phase1Opcodes Class Reference

Public Types

- enum [Opcodes](#)

3.16.1 Detailed Description

This class contains a public enum that contains symbolic names for the opcodes that define CSTA phase 1 operations.

3.16.2 Member Enumeration Documentation

3.16.2.1 enum Opcodes

Contains symbolic names for the opcodes that define CSTA phase 1 operations.

3.17 Phase2Opcodes Class Reference

Public Types

- enum [Opcodes](#)

3.17.1 Detailed Description

This class contains a public enum that contains symbolic names for the opcodes that define CSTA phase 2 operations.

3.17.2 Member Enumeration Documentation

3.17.2.1 enum Opcodes

Contains symbolic names for the opcodes that define CSTA phase 2 operations.

3.18 Phase3Opcodes Class Reference

Public Types

- enum [Opcodes](#)

3.18.1 Detailed Description

This class contains a public enum that contains symbolic names for the opcodes that define CSTA phase 3 operations.

3.18.2 Member Enumeration Documentation

3.18.2.1 enum Opcodes

Contains symbolic names for the opcodes that define CSTA phase 3 operations.

3.19 SiemensCap Class Reference

Inherits [Com::Objsys::Csta::Phase3::IETF_CSTAp3](#).

Inherited by [SiemensHipath4000](#).

Public Member Functions

- override [CSTARResponseInfo MakeACSEAssociation \(\)](#)

3.19.1 Detailed Description

Implements CSTA phase 3 operations for the Siemens CAP PBX device.

3.19.2 Member Function Documentation

3.19.2.1 override [CSTARResponseInfo MakeACSEAssociation \(\)](#) [virtual]

Establish an ACSE association with the PBX.

Returns

A [CSTARResponseInfo](#) object.

Reimplemented from [GenericCSTAp3](#).

3.20 SiemensHicom300 Class Reference

Inherits [Com::Objsys::Csta::Phase1::GenericCSTAp1](#).

Public Member Functions

- [SiemensHicom300 \(\)](#)

3.20.1 Detailed Description

Implements CSTA phase 1 operations for the Siemens Hicom 300 PBX device.

3.20.2 Constructor & Destructor Documentation

3.20.2.1 SiemensHicom300 ()

Default constructor. This device uses IETF-like prefixes plus a special application code.

3.21 SiemensHipath3000p2 Class Reference

Inherits [Com::Objsys::Csta::Phase2::GenericCSTAp2](#).

Public Member Functions

- [SiemensHipath3000p2 \(\)](#)

3.21.1 Detailed Description

Implements CSTA phase 2 operations for the Siemens Hipath 3000 PBX device.

3.21.2 Constructor & Destructor Documentation

3.21.2.1 SiemensHipath3000p2 ()

Default constructor. This device uses IETF-like prefixes plus a special application code.

3.22 SiemensHipath3000p3 Class Reference

Inherits [Com::Objsys::Csta::Phase3::GenericCSTAp3](#).

Public Member Functions

- override [CSTAResponseInfo MakeACSEAssociation \(\)](#)
- [SiemensHipath3000p3 \(\)](#)

3.22.1 Detailed Description

Implements CSTA phase 3 operations for the Siemens Hipath 3000 PBX device.

3.22.2 Constructor & Destructor Documentation

3.22.2.1 SiemensHipath3000p3 ()

Default constructor. This device uses IETF-like prefixes plus a special application code.

3.22.3 Member Function Documentation

3.22.3.1 override [CSTAResponseInfo MakeACSEAssociation \(\)](#) [virtual]

Establish an ACSE association with the PBX.

Returns

A [CSTAResponseInfo](#) object.

Reimplemented from [GenericCSTAp3](#).

3.23 SiemensHipath4000 Class Reference

Inherits [Com::Objsys::Csta::Devices::SiemensCap](#).

3.23.1 Detailed Description

Implements CSTA phase 3 operations for the Siemens Hipath 4000 PBX device.

3.24 SiemensRealitis Class Reference

Inherits [Com::Objsys::Csta::Phase1::IETF_CSTAp1](#).

3.24.1 Detailed Description

Implements CSTA phase 1 operations for the Siemens Realitis PBX device.

3.25 SingleStepTransferInfo Class Reference

Properties

- string [TransferFromDevice](#) [get, set]
- string [TransferringCallID](#) [get, set]
- string [TransferToDevice](#) [get, set]

3.25.1 Detailed Description

Contains information needed to complete a phase 3 single step transfer request.

3.25.2 Property Documentation

3.25.2.1 string TransferFromDevice [get, set]

Identification (e.g., phone number) of the device from which the call is being transferred.

3.25.2.2 string TransferringCallID [get, set]

The call id number associated with the device from which the call is being transferred.

3.25.2.3 string TransferToDevice [get, set]

Identification (e.g., phone number) of the device to which the call is being transferred.

3.26 SocketState Class Reference

Properties

- byte[] [ReadBuffer](#) [get, set]
- int [TotalLength](#) [get, set]

3.26.1 Detailed Description

This class contains the response received from the PBX and state information about the exchange with the PBX that is used internally by CSTADLL.

3.26.2 Property Documentation

3.26.2.1 byte [] [ReadBuffer](#) [get, set]

Contains the bytes read from the socket. This buffer will be filled in bit by bit as the message is read.

3.26.2.2 int [TotalLength](#) [get, set]

The total length of a complete message received from the PBX. This is also used as an offset into the read buffer so we can build the message as it's received.

3.27 TadiranCoral Class Reference

Inherits [Com::Objsys::Csta::Phase1::IETF_CSTAp1](#).

3.27.1 Detailed Description

Implements CSTA phase 1 operations for the Tadiran Coral PBX device.

3.28 TransferCallInfo Class Reference

Properties

- string [ActiveDeviceCallID](#) [get, set]
- string [ActiveDeviceNumber](#) [get, set]
- string [ConnectedDevice](#) [get, set]
- string [HeldDevice](#) [get, set]
- string [HeldDeviceCallID](#) [get, set]
- string [HeldDeviceNumber](#) [get, set]

3.28.1 Detailed Description

Contains information needed to complete a phase 3 transfer call request.

3.28.2 Property Documentation

3.28.2.1 string ActiveDeviceCallID [get, set]

The call id associated with the device to which the call is being transferred.

3.28.2.2 string ActiveDeviceNumber [get, set]

The phone number to which the call is being transferred. This number is not necessarily the same as the value for ConnectedDevice.

3.28.2.3 string ConnectedDevice [get, set]

Identification (e.g., phone number) of the device to which the call is being transferred.

3.28.2.4 string HeldDevice [get, set]

Identification (e.g., phone number) of the device from which the call is being transferred.

3.28.2.5 string HeldDeviceCallID [get, set]

The call id associated with the device from which the call is being transferred.

3.28.2.6 string HeldDeviceNumber [get, set]

The phone number from which the call is being transferred. This number is not necessarily the same as the value for HeldDevice.

Index

- AcquireControlRight
 - Com::Objsys::Csta::Devices::PanasonicKXTDE, 29
- ActiveDeviceCallID
 - Com::Objsys::Csta::Phase3::TransferCallInfo, 48
- ActiveDeviceNumber
 - Com::Objsys::Csta::Phase3::TransferCallInfo, 48
- Alcatel4400
 - Com::Objsys::Csta::Devices::Alcatel4400, 9
- AlcatelOXO
 - Com::Objsys::Csta::Devices::AlcatelOXO, 10
- AnswerCall
 - Com::Objsys::Csta::Phase1::GenericCSTAp1, 12
 - Com::Objsys::Csta::Phase2::GenericCSTAp2, 15
 - Com::Objsys::Csta::Phase3::GenericCSTAp3, 18
- AsyncCallback
 - Com::Objsys::Csta::Common::PBXSessionHelper, 33
- ClearMessageWaiting
 - Com::Objsys::Csta::Devices::PanasonicKXTDE, 29
 - Com::Objsys::Csta::Phase3::GenericCSTAp3, 18
- ClientCallback
 - Com::Objsys::Csta::Common::PBXSessionHelper, 35
- Close
 - Com::Objsys::Csta::Common::PBXSessionHelper, 33
- Com.Objsys.Csta.Common, 3
- Com.Objsys.Csta.Devices, 4
- Com.Objsys.Csta.Phase1, 5
- Com.Objsys.Csta.Phase2, 6
- Com.Objsys.Csta.Phase3, 7
- Com::Objsys::Csta::Common::CSTAResponseInfo, 11
 - ResponseFromPBX, 11
 - StatusCode, 11
 - StatusMessage, 11
- Com::Objsys::Csta::Common::LicenseException, 27
- Com::Objsys::Csta::Common::PBXSessionException, 32
- Com::Objsys::Csta::Common::PBXSessionHelper, 33
 - AsyncCallback, 33
 - ClientCallback, 35
 - Close, 33
 - DebugMode, 35
 - Init, 33
 - LoggingEnabled, 35
 - LoggingFolder, 35
 - Open, 34
 - SendMessage, 34
 - WaitForACSEResponse, 34
 - WaitForROSEResponse, 34
- Com::Objsys::Csta::Common::SocketState, 46
 - ReadBuffer, 46
 - TotalLength, 46
- Com::Objsys::Csta::Devices::Alcatel4400, 9
 - Alcatel4400, 9
 - MakeACSEAssociation, 9
- Com::Objsys::Csta::Devices::AlcatelOXO, 10
 - AlcatelOXO, 10
 - MakeACSEAssociation, 10
- Com::Objsys::Csta::Devices::PanasonicKXTDA, 28
- Com::Objsys::Csta::Devices::PanasonicKXTDE, 29
 - AcquireControlRight, 29
 - ClearMessageWaiting, 29
 - MakeACSEAssociation, 29
 - ReleaseControlRight, 30
 - SetMessageWaiting, 30
- Com::Objsys::Csta::Devices::PanasonicNCP, 31
- Com::Objsys::Csta::Devices::SiemensCap, 39
 - MakeACSEAssociation, 39
- Com::Objsys::Csta::Devices::SiemensHicom300, 40
 - SiemensHicom300, 40
- Com::Objsys::Csta::Devices::SiemensHipath3000p2, 41
 - SiemensHipath3000p2, 41
- Com::Objsys::Csta::Devices::SiemensHipath3000p3, 42
 - MakeACSEAssociation, 42
 - SiemensHipath3000p3, 42
- Com::Objsys::Csta::Devices::SiemensHipath4000, 43
- Com::Objsys::Csta::Devices::SiemensRealitis, 44
- Com::Objsys::Csta::Devices::TadiranCoral, 47
- Com::Objsys::Csta::Phase1::GenericCSTAp1, 12
 - AnswerCall, 12
 - DivertCall, 12
 - EncodeROSERequestHeader, 13
 - GenericCSTAp1, 12
 - MakeACSEAssociation, 13
 - MakeCall, 13
 - MonitorStart, 13
 - MonitorStop, 13
 - QueryDevice, 14
 - TransferCall, 14

Com::Objsys::Csta::Phase1::IETF_CSTAp1, 24
 IETF_CSTAp1, 24
 Com::Objsys::Csta::Phase1::Phase1Opcodes, 36
 Opcodes, 36
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 15
 AnswerCall, 15
 DivertCall, 15
 EncodeROSERequestHeader, 16
 GenericCSTAp2, 15
 MakeACSEAssociation, 16
 MakeCall, 16
 MonitorStart, 16
 MonitorStop, 17
 QueryDevice, 17
 TransferCall, 17
 Com::Objsys::Csta::Phase2::IETF_CSTAp2, 25
 IETF_CSTAp2, 25
 Com::Objsys::Csta::Phase2::Phase2Opcodes, 37
 Opcodes, 37
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 18
 AnswerCall, 18
 ClearMessageWaiting, 18
 EncodeROSERequestHeader, 19
 GenericCSTAp3, 18
 GetSFDevices, 19
 MakeACSEAssociation, 19
 MakeCall, 19
 MonitorStart, 20
 MonitorStop, 20
 ReleaseACSEAssociation, 20
 RingDevice, 20
 SendData, 21
 SetDisplay, 21
 SetMessageWaiting, 21
 SingleStepTransfer, 21
 StartDataPath, 22
 StopDataPath, 22
 StopRing, 22
 TransferCall, 22
 Com::Objsys::Csta::Phase3::IETF_CSTAp3, 26
 IETF_CSTAp3, 26
 Com::Objsys::Csta::Phase3::Phase3Opcodes, 38
 Opcodes, 38
 Com::Objsys::Csta::Phase3::SingleStepTransferInfo, 45
 TransferFromDevice, 45
 TransferringCallID, 45
 TransferToDevice, 45
 Com::Objsys::Csta::Phase3::TransferCallInfo, 48
 ActiveDeviceCallID, 48
 ActiveDeviceNumber, 48
 ConnectedDevice, 48
 HeldDevice, 48
 HeldDeviceCallID, 48
 HeldDeviceNumber, 48
 ConnectedDevice
 Com::Objsys::Csta::Phase3::TransferCallInfo, 48
 DebugMode
 Com::Objsys::Csta::Common::PBXSessionHelper, 35
 DivertCall
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 12
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 15
 EncodeROSERequestHeader
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 13
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 16
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 19
 GenericCSTAp1
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 12
 GenericCSTAp2
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 15
 GenericCSTAp3
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 18
 GetSFDevices
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 19
 HeldDevice
 Com::Objsys::Csta::Phase3::TransferCallInfo, 48
 HeldDeviceCallID
 Com::Objsys::Csta::Phase3::TransferCallInfo, 48
 HeldDeviceNumber
 Com::Objsys::Csta::Phase3::TransferCallInfo, 48
 IETF_CSTAp1
 Com::Objsys::Csta::Phase1::IETF_CSTAp1, 24
 IETF_CSTAp2
 Com::Objsys::Csta::Phase2::IETF_CSTAp2, 25
 IETF_CSTAp3
 Com::Objsys::Csta::Phase3::IETF_CSTAp3, 26
 Init
 Com::Objsys::Csta::Common::PBXSessionHelper, 33
 LoggingEnabled
 Com::Objsys::Csta::Common::PBXSessionHelper, 35
 LoggingFolder
 Com::Objsys::Csta::Common::PBXSessionHelper, 35
 MakeACSEAssociation
 Com::Objsys::Csta::Devices::Alcatel4400, 9
 Com::Objsys::Csta::Devices::AlcatelOXO, 10
 Com::Objsys::Csta::Devices::PanasonicKXTDE, 29
 Com::Objsys::Csta::Devices::SiemensCap, 39
 Com::Objsys::Csta::Devices::SiemensHipath3000p3, 42

Com::Objsys::Csta::Phase1::GenericCSTAp1, 13
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 16
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 19
MakeCall
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 13
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 16
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 19
MonitorStart
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 13
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 16
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 20
MonitorStop
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 13
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 17
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 20
Opcodes
 Com::Objsys::Csta::Phase1::Phase1Opcodes, 36
 Com::Objsys::Csta::Phase2::Phase2Opcodes, 37
 Com::Objsys::Csta::Phase3::Phase3Opcodes, 38
Open
 Com::Objsys::Csta::Common::PBXSessionHelper, 34
QueryDevice
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 14
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 17
ReadBuffer
 Com::Objsys::Csta::Common::SocketState, 46
ReleaseACSEAssociation
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 20
ReleaseControlRight
 Com::Objsys::Csta::Devices::PanasonicKXTDE, 30
ResponseFromPBX
 Com::Objsys::Csta::Common::CSTAResponseInfo, 11
RingDevice
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 20
SendData
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 21
SendMessage
 Com::Objsys::Csta::Common::PBXSessionHelper, 34
SetDisplay
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 21
SetMessageWaiting
 Com::Objsys::Csta::Devices::PanasonicKXTDE, 30
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 21
SiemensHicom300
 Com::Objsys::Csta::Devices::SiemensHicom300, 40
SiemensHipath3000p2
 Com::Objsys::Csta::Devices::SiemensHipath3000p2, 41
SiemensHipath3000p3
 Com::Objsys::Csta::Devices::SiemensHipath3000p3, 42
SingleStepTransfer
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 21
StartDataPath
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 22
StatusCode
 Com::Objsys::Csta::Common::CSTAResponseInfo, 11
StatusMessage
 Com::Objsys::Csta::Common::CSTAResponseInfo, 11
StopDataPath
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 22
StopRing
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 22
TotalLength
 Com::Objsys::Csta::Common::SocketState, 46
TransferCall
 Com::Objsys::Csta::Phase1::GenericCSTAp1, 14
 Com::Objsys::Csta::Phase2::GenericCSTAp2, 17
 Com::Objsys::Csta::Phase3::GenericCSTAp3, 22
TransferFromDevice
 Com::Objsys::Csta::Phase3::SingleStepTransferInfo, 45
TransferringCallID
 Com::Objsys::Csta::Phase3::SingleStepTransferInfo, 45
TransferToDevice
 Com::Objsys::Csta::Phase3::SingleStepTransferInfo, 45
WaitForACSEResponse
 Com::Objsys::Csta::Common::PBXSessionHelper, 34
WaitForROSEResponse
 Com::Objsys::Csta::Common::PBXSessionHelper, 34